

CAT. N° 3 106 65



## EMPTY BATTERY CABINET FOR CAT.NO 310170

Pack (number of units)	1
Volume (dm <sup>3</sup> )	108,653
Weight (g)	11 827,00

### Product characteristics

#### Battery cabinet (empty)

- Battery cabinet for Cat.No 3 101 70

### General characteristics

#### DAKER DK PLUS - On-line double conversion UPS (rack/tower) - single phase and three phase VFI

- The main parameters of the UPS, including the battery charge level and faults, are displayed on the LCD screen on the front panel
- The integrated communication software not only controls the UPS and its switch-off if there is a malfunction, and enables the user to test the main functions remotely, communicate via SNMP/Internet/network adaptor and access the functions of the UPS via the Internet, but can also send the user an SMS if specific events occur
- The internal extension connector enables aWEB/SNMP card or a relay interface to be installed which provides insulated contacts for applications on industrial control panels or remote alarm panels
- If there is an electronic fault, overload, overheating or for scheduled maintenance operations, the automatic or manual (optional) bypass ensures continuity of the power supply for critical loads. A bypass switch is available for maintenance

### Documentation

#### Catalogue pages & additional information

- [Technical page \(p.708\)](#)
- [Description page \(p.707\)](#)
- [DAKER DK PLUS](#)