

CAT. N° 4 149 36



## STAND ALONE CONFIGURATION MODULES CX<sup>3</sup> - RAIL MOUNTING - 4 MODULES

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,716
Weight (g)	143,00

### Product characteristics

#### Stand alone configuration module

##### Rail mounting

- Enables upstream busbar connection
- Optional module for "stand alone" supervision need
- Enables to configure, test and control CX<sup>3</sup> energy management system and to visualize supervision data
- No computer or IP connection required
- Consumption: 0.438 W - 36.5 mA (12 V =)
- Number of modules : 4

### General characteristics

#### CX<sup>3</sup> energy management system

- Conform to IEC/EN 61131-2 (Programmable controllers)
- CX<sup>3</sup> energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX<sup>3</sup> and DPX<sup>3</sup>), locally ("Stand alone" ) or remotely
- All the modules of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)
- Power supply with specific module Cat.No 4 149 45
- Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.101\)](#)

#### Installation & technical data

- [F02340EN-02](#)

#### Installation instructions & related documents

- [LE08387AB](#)

#### Softwares

- [Legrand Energy Management Software](#)