

CAT. N° 4 149 03



COMMUNICATION RAIL CX3 - FOR RAIL OR SPACER - 36 MODULES

Pack (number of units)	1
Volume (dm³)	0,531
Weight (g)	126,00

Product characteristics

Connection accessories

Communication rails

- To be fitted on rail or spacer
- \blacksquare Allows data transmission between the different modules of CX^{3} energy supervision system
- For other lengths, please consult us
- 36 modules

General characteristics

CX3 energy management system

- Conform to IEC/EN 61131-2 (Programmable controllers)
- CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely
- All the modules of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)
- Power supply with specific module Cat.No 4 149 45
- Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.

Documentation

- Catalogue pages & additional information
 - Description page (p.101)
- 🔳 Installation & technical data
 - F02339EN-02

- Softwares
 - Legrand Energy Management Software

^{*} All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis: before-tax price list, May 2018