

CAT. N° 0 425 81



## ISOLATING TRANSFO FOR HOSPITALS -3 PHASE- PRIM 400 V / SEC 230 V -OUTPUT 4 KVA

Pack (number of units)	1
Volume (dm <sup>3</sup> )	198,38
Weight (g)	61 000,00

### Product characteristics

#### 3-phase

**Primary: 400 V~ + N / Secondary: 230 V~ + N**

- Equipped with a temperature monitoring system (bi-metal strips) for connection to a control system (optical, acoustic, etc...)
- IP 21
- Output : 4 kVA
- Terminal primary flexible cable : 10 mm<sup>2</sup>
- Terminal secondary flexible cable : 10 mm<sup>2</sup>

### General characteristics

#### Isolating transformers for hospitals

- Conform to standard IEC EN 61558-2-15
- The main requirements of this standard, additionally to IEC 61558-2-4, concern:
  - secondary/earth leakage current, limited to 0.5 mA off-load
  - inrush current, limited to 12 times the peak value of primary current
- Electrostatic shield linked to dedicated terminal
- Equipped with a temperature monitoring system, and outputs on dedicated terminals

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.917\)](#)



#### Installation & technical data

- [F00725EN/03](#)