

CAT. N° 4 149 29



STATE REPORTING MODULESULE CX³ - AUXILIARY + FAULT SIGNALLING CONTACT - 0.5 MODULE

Pack (number of units)	1
Volume (dm ³)	0,229
Weight (g)	55,00

Product characteristics

State reporting modules

Auxiliary + fault signalling contact

- Enables upstream busbar connection
- Indicates the position of the contacts and the fault tripping of its associated device.
- To fit on the left-hand side of DX3 MCBs, RCCBs, RCBOs and isolating switches
- Consumption: 0.236 W - 19.7 mA (12 V =)
- Number of modules : 0.5

General characteristics

CX³ energy management system

- Conform to IEC/EN 61131-2 (Programmable controllers)
- CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely
- All the modules of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)
- Power supply with specific module Cat.No 4 149 45
- Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Documentation



Catalogue pages & additional information

- [Description page \(p.100\)](#)



Installation & technical data

- [F02334EN-02](#)
- [MODBUS TAB 414929](#)



Installation instructions & related documents

- [LE08383AC](#)



Softwares

- [Legrand Energy Management Software](#)