

# **Product sheet**



#### **LEGRAND**

Device for emergency exit - 2 NO/NC - 5 A - 24 V= - RAL 6016

REF. 138048 | EAN. 3414970520494

> Visit e-catalogue

### **Product characteristics**

- · Safety boxes 90 series for fire detection and fire alarm system, emergency exit, extinguishing system, remote switching
- Manual call points (MCP) IP 30 IK 07 Surface mounting or flush-mounting (IP 30) Dimensions: 90x90x57 mm (surface mounting with its base) or 90x90x24 mm (flush-mounting with flush boxes for wiring devices drilling diameter 67 mm for 60 mm Fixing centres) Can be fitted on trunking Cat. Nos 0 104 63/64, 35x105 mm or 50x105 mm, with the universal support Cat. No 0 109 13 Call by pressing the membrane (pressure 2.5 kg) with clear display of the call position Reset on Front of device, with special key Cat. No 0 380 38 (supplied with the product) Possibility to add an optional mechanical status indicator Cat. No 1 380 93 to provide additional signalling Can receive a sealable cover Cat.No 0 380 97 devices for emergency exit (DCMIS) Allow the immediate release of an exit door normally closed by an electromagnetic lock Color of the mechanical enclosure: green RAL 6016 DCMIS 2 contacts Equipped with 2 NO/NC contacts 5 A 24 VDC Second contact can be used to trigger: a technical alarm a CCTV camera (visually and recording allows remote viewing and recording of any malicious act)

## Documentation

### **TECHNICAL DOCUMENTATION**

→ LE07337AC.pdf | PDF (2.95Mo)

CAD & Design specs / BIM

**1** 3D\_LG-138048.stp | IFC (1.42Mo)

### **CATALOGUE PAGE & OTHERS**

ex223001\_0919.pdf | PDF (0.07Mo)