# **Product sheet**



#### DMX<sup>3</sup> 2500 LEGRAND

Circuit breaker DMX<sup>3</sup> 2500, 4 poles, fixed version and electronic protection unit

REF. 028372 | EAN. 3414972325745

> Visit e-catalogue

#### **Product characteristics**

- Breaking capacity of 42kA, according to EN/IEC standard 60947 - 2, suitable for protection of high power industrialinstallations. Rated insulation voltage of 1000VRated impulse withstand voltage of 12kV
- Climatic condition according to IEC/EN 60947 1 Annex Q, Cat. F subject to temperature,humidity, vibration, shock and salt mist.
- Electronic protection module ot type MP2.10 (LED matrix display) or MP4.10 (LCD screen) for common for measurements and settings. Thermal and magnetic protections completely adjustable in times and currents by dedicated software
- Can be equipped with releases (undervoltage and shunt releases) and auxiliary contacts.Can used with rotary handles or motor operator.Locking accessories are available.
- Has diffent type of possible connection accessories: cage terminals, spreader and rear terminals. Is available also in a plug-in version (circuit breaker fitted with special terminals and mountedon a plug-in base) or in a draw-out version (a plug-in version fitted with a"Debro-lift" mechanism which can be used to withdraw the breaker whilekeeping it on its base)

# Documentation

### TECHNICAL DOCUMENTATION

Cahier d'atelier : Disjoncteurs et interrupteurs DMX<sup>3</sup> et DMX<sup>3</sup>-I | PDF (89.51Mo)

Workshop Book: DMX<sup>3</sup> and DMX<sup>3</sup>-I air circuit breakers and trip free-switches | PDF (88.07Mo)

**F03884EN\_01.pdf** | PDF (6.07Mo)

# The product's benefits

#### Installation

 Electric and mechanical robustness, in addiction to breaking capacity and chances of accessorizing, are perfectly suited for increase continuity service looking at the plant energy efficiency and in respect of "green aspects"

#### Usage

 DMX<sup>3</sup> platform provide a complete "project" approach in premiummarket segment, offering a range completely suitable for high powerapplication

### **CATALOGUE PAGE & OTHERS**

- ex223001\_0216.pdf | PDF (0.1Mo)
- ex223001\_0234-0235.pdf | PDF (0.1Mo)
- ex223001\_0230-0231.pdf | PDF (0.97Mo)
- ex223001\_0228-0229.pdf | PDF (1.14Mo)

# **L** legrand<sup>®</sup>

- MODBUS\_MAPS.pdf | PDF (1.12Mo)
- E LE12614AA.pdf | PDF (52.72Mo)
- **F03884FR\_00.pdf** | PDF (5.97Mo)
- → LE08866AC.pdf | PDF (6.7Mo)

## Agreements & Certificates

PEP\_LGRP-01939-V01.01-EN.pdf | PDF (0.82Mo)

ex223001\_0233.pdf | PDF (0.04Mo)

## Software & configurators

PowerControlStation 5.0.0.78.zip | ZIP (52.57Mo)