

CAT. N° 4 062 52



FAULT SIGNALLING CONTACT DX³ - 6 A 250 V~ - 0.5 MODULE

Pack (number of units)	1
Volume (dm ³)	0,219
Weight (g)	52,00

Product characteristics

Signalling auxiliaries fork busbar adapted

- To fit on the left-hand side of DX³ and TX³ devices
- Maximum number of auxiliaries per device:
 - 3 signalling auxiliaries or
 - 2 signalling auxiliaries + 1 remote tripping auxiliary
- Allow insertion of the supply busbar, top side
 - No tool required for joining together the auxiliary and the main device.
- No tool required for joining together the auxiliary and the main device.

Auxiliary contact

- 6 A - 250 V~ (changeover switch)
- For MCBs, RCBOs, RCCBs, isolating switch or remote trip isolating switch
- Indicates the position of the contacts of its associated device
- Fault signalling contact
- 6 A - 250 V~ (changeover switch)
- For MCBs, RCBOs, RCCBs,
- Indicates the fault tripping of its associated device
- Number of modules : 0.5

General characteristics

Signalling, remote tripping auxiliaries and motorised controls DX³

Documentation



Catalogue pages & additional information

- [Description page \(p.072\)](#)
- [Dimensions of din-rail equipment](#)



Installation & technical data

- [F01548EN-00](#)



Installation instructions & related documents

- [LE04412AF](#)